

PRODUCT

ESD Printed Floor Tape

TECHNICAL DATASHEET



DESCRIPTION

Our highly visible, yellow floor marking tape is printed in black with the ESD caution logo and is ideal for marking EPA boundaries. The tape is self-adhesive and adheres well to synthetic and clean, particle-free floors such as concrete, metals, high surface energy and low surface energy plastics. The tape can be expected to remain intact for several months depending on traffic



FEATURES

- Ideal for applications requiring high initial tack, especially on low surface energy plastics
- Bright yellow with black ESD logo (EN61340-5-1 compliant) and 'ESD Protected Area' text
- Laminated with a clear film to protect print
- Clearly marks EPA boundaries with high visibility
- Highly resistant to abrasion and chemicals
- **Not** antistatic – designed for use outside the EPA

PRODUCT CODE	DESCRIPTION	SIZE (METRIC)	SIZE (IMPERIAL)	QUANTITY
054-0007	ESD Floor Marking Tape	72mm x 33m	2.8in x 108.3ft	Each

To request a quotation or for more information, please call **+44 (0)1473 836200**
email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2025 Antistat.

CONSTRUCTION

- 32 Micron PVC base
- 20 Microns of Natural Rubber, Solvent Adhesive
- 25 Micron BOPP Laminate with Thermostable Acrylic Adhesive

TECHNICAL DATA

MEASURE	UNIT	RESULT & TOLERANCE
Carrier Thickness	Microns	74 +/- 5%
Adhesive weight	GSM	18 +/- 5%
Total thickness	Microns	93 +/- 5%
Peel adhesion (Afera 5001) Steel	Newtons/25mm	3.5 +/- 5%
Elongation (Afera 5004)	%	<4
Service Temperature	Tape can withstand	18-85°C
Application Temperature	At the point of application	>+18°C

NOTES

Tape performance is guaranteed for the first 6 months. Product must be stored at ambient temperature (Between 18°C-23°C), in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the batch identification number printed on the box. For optimum performance stock should be rotated and used within 12 months. The tapes have adhesive that are pressure sensitive so must be properly applied to ensure the best performance.

Physical and performance characteristics shown above are obtained following tests recommended by AFERA and PSTC. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

To request a quotation or for more information, please call **+44 (0)1473 836200**
 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2025 Antistat.