

PRODUCT

Surface Resistance Meter

TECHNICAL DATASHEET

DESCRIPTION

 $10 v \ / \ 100 v$ point-to-point surface resistivity and resistance to ground testing meter, ideal for testing EPA to the latest industry standards.

FEATURES

Supplied in a conductive carry case

SPECIFICATIONS			
Method of Measurement	Surface resistivity (Ohms per square) Point to point (Ohms)		
Indicators	Conductive - green LED 10³ - 10⁵ Ohms		
	Static Dissipative - yellow LED 10 ⁶ – 10 ⁹ Ohms	Static Dissipative - orange LED 10º – 10¹º Ohms	
	Insulative - red LED >10 ¹¹ Ohms		
Relative Humidity	0% to 90% (non-condensing)		
Accuracy	+/- 0.5 decade in conductive range +/- 0.25 decade in dissipative range		
Repeatability	+/- 10%		
Weight	150g		
Dimensions	130mm x 70mm x 25mm		
Power Supply	9 volt PP3 alkaline battery		
Test Voltage	Nominal 9 volts-stepped to 100 volts		
Test Range	1K Ohms (10³) to 1TΩ (10¹²) Displayed in 1/2 decade steps		
Temperature Range	Operating 5°C to 49°C (40°F to 120°F) Storage -15°C to +60°C		

To request a quotation or for more information, please call +44 (0)1473 836200 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheets should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2024 Antistat.



USER GUIDE

Testing and auditing all elements within the EPA is essential to comply with industry standards. The Surface Resistivity Kit has been designed specifically for the purpose of testing surfaces used in an EPA and measures in Ohms per Square and meets the requirements of IEC 613340-5-1/2 and EN100015/1 European standard. Automatic auto ranging 10v and 100v test voltages are incorporated into the tester, switching as you move from conductive, dissipative and insulative surfaces.

The meter is also capable of testing resistance to ground and point to point resistance.

SET-UP AND OPERATIONS

- 1. Fit the supplied 9V battery; the battery compartment is located at the rear of the enclosure. The unit is now ready to use. If at any time the battery voltage drops below 6.5 volts the blue battery low indicator will not illuminate during the test.
- 2. To test surface resistance place the unit on the surface to be tested and press the test button.
- 3. To measure resistance to ground insert one of the supplied test leads into one of the two 3.5mm sockets, located on the top panel of the meter, attaching the other end on your ground point. Press the test button.
- 4. To measure the point to point resistance insert the 3.5mm jack plug test leads into the 2 x 3.5mm jack sockets located on the top panel of the meter. Connect the two 2.5kg (51b) weights, to the other end of the test leads via the 4mm banana plugs (red & black). Place the weights gently onto the surface that requires testing. Press the test button.
- GREEN LEDs indicate a conductive reading. Measurements are taken at a test voltage of 10V. YELLOW / ORANGE LEDs indicate a dissipative reading. Measurements are taken automatically at a test voltage of 100 volts. RED LEDs indicate an insulative reading. Measurements are taken automatically at a test voltage of 100 volts.

PRODUCT CODE	DESCRIPTION	SIZE (mm)	NOTES
093-0089	Surface Resistant Meter 100V	130 x 70 x 25	Each

To request a quotation or for more information, please call +44 (0)1473 836200 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antitate or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Llability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of users of the loss or damage arising) is excluded. © 2024 Antistat.