

Top Gun™ Sidekick

FEATURES:

- Flexible neck feature frees the operator's hands during assembly and manufacturing processes.
- Flexible gun mount allows the operator to focus the ionised airflow where it is needed.
- A foot pedal controls both ionisation and airflow, which reduces compressed air costs and extends the life of the ioniser.
- The stand includes a steel bracket for easy bench-top mounting.

CONSISTS OF:

- Top Gun Ionising Air Gun
- Foot Pedal
- 18" Flexible Hose
- Mounting Bracket

CONSTRUCTION:

- Gun: static dissipative
- Polycarbonate / ABS alloy
- Cable: static dissipated polyurethane



WEIGHT	Gun: 6.5 oz (185g) Cable: 1.25 oz/ft (115g/m)
POWER UNIT SIZE (H x W x D)	6.45 x 5.20 x 3.35 in., 164 x 132 x 85 cm
POWER INLET	IEC320
AIR INLET	1/8 NPT (female)
INPUT PRESSURE	100psi (7 bar) maximum, clean dry air or nitrogen.
AIR CONSUMPTION	2.4SCFM at 30psi (68l/min at 2 bar), 4.6SCFM at 60psi (130l/min at 4 bar), 7.4SCFM at 100psi (210l/min at 7bar)
OUTPUT PRESSURE	Pressure relief in nozzle, complies with OSHA requirements.
REPLACEMENT FILTER	0.01 micron
OPERATING TEMP.	32°F (0°C) – 104°F (40°C)
OFFSET VOLTAGE	0 ± 15V
DISCHARGE TIME	1.3secs at 6 in. and 30psi, 0.5secs at 2 in. and 60psi
AUDIBLE NOISE (MEASURED 24 IN. (600MM) FROM NOZZLE)	76dB at 30psi (2 bar) 89dB at 30psi (4 bar) 97 dB at 100psi (7bar)

PRODUCT CODE:	CABLE LENGTH:	LINE VOLTAGE:	FREQUENCY:	LINE CURRENT (AT REST):	LINE CURRENT (OPERATION):
4005105	7 ft. (2.13 m)	120VAC	50/60Hz	0.01 Amps	0.10 Amps
4006599	14 ft. (4.26 m)	120VAC	50/60Hz	0.01 Amps	0.10 Amps
4005106	7 ft. (2.13 m)	230VAC	50/60Hz	0.005 Amps	0.05 Amps
4006600	14 ft. (4.26 m)	230VAC	50/60Hz	0.005 Amps	0.05 Amps

PRODUCT CODE:	DESCRIPTION:	ADDITIONAL NOTES:
TBC	Top Gun™ Sidekick	Each