


**PRODUCT**

# Static shielding bag - Open top

**ANT010SSB**

These open top, easy access static shielding bags are designed to protect sensitive electronic devices against ESD during transit and whilst kept in storage.



**FEATURES**

- Metal “Faraday cage” layer shields products from electric energy inside and prevents static build-up
- Four layer protection guards against charges inside and out
- Semi transparent for easy content identification
- Surface resistance of  $10^6$ - $10^{10}$  Ohms
- Conforms to EIA 625, EIA 541, ANSI/ESD S-20.20
- Custom sizes and print available on request
- Suitable for packing electronic products which are sensitive to static, eg PCBs, electronic components etc

**1) CONFIGURATION(S)**

Our bags are available in custom sizes or in several industry standard sizes. Bags are offered in a 2-seal configuration and bottom fold, with our standard flexographically printed artwork. Please note any bags that are longer than 24” will have a 3rd seal along the bottom edge.

**2) BAG ARTWORK**

Our static shielding bags are produced with the shown artwork as standard. For further information on bespoke/ printed orders, please contact one of our sales team.

To request a quotation or for more information, please call **+44 (0)1473 836200** email [info@antistat.co.uk](mailto:info@antistat.co.uk) or visit [www.antistat.co.uk](http://www.antistat.co.uk)


IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2021 Antistat.

### 3) CONSTRUCTION

Our static shielding bags are constructed in four layers, consisting of a static dissipative polyester outer layer and a static dissipative polyethylene inner layer with a centre metallised shield layer.

Our bags are manufactured from industry approved polyester and polyethylene laminates. The polyester dielectric works with the metal layer to provide a Faraday effect, the metal layer preventing penetration from damaging electrostatic fields.

The specially processed polyethylene keeps tribocharging to a minimum.



### TEST CONDITIONS

The following results were taken under the following environmental test conditions: Temperature: 23°C / Humidity: 12% RH.

ITEM	TEST METHOD	TYPICAL VALUE
Film thickness	Micron Meter	3Mil 75 micron
Metal layer optical transmission	ASTM D1003 (TOBIAS)	40% +/- 5% optical density
Surface resistivity	STM 11.11	10 <sup>6</sup> -10 <sup>10</sup>
Time for static removal	FTMS 101B Method 4046 - 5000-0V	<.03 Sec
Static shielding - Energy penetration	ESD-STM-11.31 @12% R.H.	<20 nJ
Static shielding - Capacitive probe	EIA 541 Appendix E	<25V
Friction static	E1A541 Appendix C Avg.	Triboelectric nanocoulombs Quartz +0.01 Tefion -0.09
Anti-erosion	FTMS 101C Method 3005	No visible spots
Tensile strength	ASTM D882-91, Method A	MD 6530 psi TD 5800 psi
Tear initiation	ASTM D1004 -94-Notched	MD 2.5 lbs./in TD 2.0 lbs
Puncture resistance	ASTM D3420	>10 psi
Tear resistance	ASTM D882	>8 psi
Burst strength	FTMS 101 C Method 2065.1	50 psi nominal
Heat seal temperature	-	250 - 375 °F
Heat seal pressure	-	30-70 PSI
Heat seal strength	(D1876-93) Vertrod bar sealer/heat	>12 lbs/in width (room temperature)
Breaking elongation rate	ASTM D882-91 Method A	MD 80% TD 85%
Appearance	-	No delamination, burst seal, wrinkle, warp, break, foreign particle adherence, air bubble beyond sealing ≤3mm

To request a quotation or for more information, please call **+44 (0)1473 836200**  
 email [info@antistat.co.uk](mailto:info@antistat.co.uk) or visit [www.antistat.co.uk](http://www.antistat.co.uk)

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2021 Antistat.

**TEST CONDITIONS**

The shielding bag is tested accordance with the relevant test standard and requirements.

TEST ITEM	TEST METHOD	MEASURED EQUIPMENT(S)	MDL
Lead (Pb)	IEC 62321:2008 Ed.1 Sec.8	ICP-OES	2mg/kg
Cadmium (Cd)	IEC 62321:2008 Ed.1 Sec.8	ICP-OES	2mg/kg
Mercury (Hg)	IEC 62321:2008 Ed.1 Sec.7	ICP-OES	2mg/kg
Hexavalent Chromium (Cr(VI))	IEC 62321:2008 Ed.1 Annex C	UV-Vis	2mg/kg
Polybrominated Biphenyls (PBBs)	IEC 62321:2008 Ed.1 Annex A	GC-MS	5mg/kg
Polybrominated Diphenyl Ethers (PBDEs)	IEC 62321:2008 Ed.1 Annex A	GC-MS	5mg/kg

PRODUCT CODE	SIZE (inch)	SIZE (mm)	QUANTITY (per pack)
010-0085	2 x 6	50.8 x 152	100
010-0001	3 x 5	76 x 127	100
010-0005	4 x 6	102 x 152	100
010-0008	4 x 12	102 x 305	100
010-0009	4 x 24	102 x 610	100
010-0013	4 x 27	102 x 685.8	100
010-0187	5 x 7	127 x 177.8	100
010-0011	5 x 8	127 x 203	100
010-0012	5 x 26	127 x 660.4	100
010-0014	6 x 8	152 x 203	100
010-0015	6 x 10	152 x 254	100
010-0016	6 x 12	152 x 305	100
010-0075	6 x 14	152 x 356	100
010-0018	6 x 30	152 x 762	100
010-0021	7 x 16	177.8 x 406	100
010-0024	8 x 10	203 x 254	100

To request a quotation or for more information, please call **+44 (0)1473 836200**  
 email [info@antistat.co.uk](mailto:info@antistat.co.uk) or visit [www.antistat.co.uk](http://www.antistat.co.uk)

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2021 Antistat.

PRODUCT CODE	SIZE (Inches)	SIZE(mm)	QUANTITY (per pack)
010-0025	8 x 12	203 x 305	100
010-0022	8 x 20	203 x 508	100
010-0027	8 x 30	203 x 762	100
010-0029	10 x 12	254 x 305	100
010-0030	10 x 14	254 x 355	100
010-0031	10 x 16	254 x 406	100
010-0040	12 x 14	305 x 355	100
010-0041	12 x 16	305 x 406	100
010-0042	12 x 18	305 x 457	100
010-0048	14 x 18	355 x 457	100
010-0097	14 x 24	355 x 610	100
010-0055	16 x 18	406 x 457	100
010-0056	16 x 20	406 x 508	100
010-0058	18 x 18	457 x 457	100
010-0059	18 x 20	457 x 508	100
010-0060	18 x 24	457 x 610	100
010-0096	20 x 24	508 x 610	100
010-0067	20 x 30	508 x 762	100
010-0006	4 x 8	102 x 203	100
010-0007	4 x 15	102 x 381	100
010-0075	6 x 14	152 x 356	100

## NOTES

- Other sizes available upon request, minimum order quantities apply
- All of Antistat's products are RoHS 3 and Reach compliant
- Supports EN 61340-5-1 and can be used as part of an ANSI/ESD S20.20

To request a quotation or for more information, please call **+44 (0)1473 836200**  
 email [info@antistat.co.uk](mailto:info@antistat.co.uk) or visit [www.antistat.co.uk](http://www.antistat.co.uk)

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2021 Antistat.