



PRODUCT

13 Inch Antistatic Plastic Reels

TECHNICAL DATASHEET

DESCRIPTION


Our 13in (330mm) plastic reels consist of two flanges plus an integral hub. Ideal for the shipment and storage of any component loaded in carrier tape.

SHELF LIFE AND STORAGE

Reels should be stored in original packaging in a climate-controlled environment where the temperature ranges from 20°C - 30°C (68°F - 86°F) with a relative humidity of 50%±10%

FEATURES

- Available in variety of widths
- Sold per half
- Easy to assemble
- Hub diameter 100mm±0.5%
- EIA standard carrier tape widths



PROPERTIES	TYPICAL VALUE	TEST METHOD
Type	Assembly (two flanges plus hub)	-
Material	High Impact Polystyrene	-
Surface Resistance	1 x 10 ⁵ to 1 x 10 ¹¹ ohms	ANSI/ESD STM11.13:2021

To request a quotation or for more information, please call **+44 (0)1473 836200**
email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2026 Antistat.


CUSTOMISATION

These 13" plastic reels are sold per half. This means that different combinations can create up to 9 different reel widths, ensuring you have the perfect reel for your application. Refer to the table below on which recommended combinations are possible.

REEL WIDTH (MM)	COMBINATIONS
8	4mm + 4mm
12	4mm + 8mm
16	8mm + 8mm
24	8mm + 16mm
32	16mm + 16mm
44	16mm + 28mm
56	28mm + 28mm
72	28mm + 44mm
88	44mm + 44mm

INTERLOCKING HALVES

Reel halves easily interlock with a simple twisting motion, eliminating the need for gluing or fasteners.



PRODUCT CODE	REEL DIAMETER	HUB DIAMETER (±0.5%)	HUB WIDTH (MM)
029-2090	330mm (13in)	100mm (3.93in)	4
029-2091			8
029-2092			16
029-2093			28
029-2094			44

To request a quotation or for more information, please call **+44 (0)1473 836200**
 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2026 Antistat.