


PRODUCT

ESD Wrist Strap On-Line Monitor and Tester





The monitor meets the continuous monitor requirements of ANSI/ESD S20.20. "Typical test programs recommend that wrist straps that are used daily should be tested daily. However, if the products that are being produced are of such value that knowledge of a continuous, reliable ground is needed, and then continuous monitoring should be considered or even required." (ESD Handbook ESD TR20.20 Wrist Strap section 5.3.2.4.4 Test Frequency)



FEATURES

- Compatible with single-wire wrist straps
- Easy to use
- Easy to install
- Fully automatic

Monitor type	Impedence - single wire		
Circuity	Solid state, surface mount		
Alarm	Audible and visable (LED)		
Alarm threshold	8 megohms		
Power	120VAC, 230VAC		
Adjustments None required			

PRODUCT CODE	DESCRIPTION	SIZE (inch)	WEIGHT (Oz)	QUANTITY
093-1010	Wrist strap monitor and tester	1 x 2.4 x 2.3	1.6 oz	Each

To request a quotation or for more information, please call +44 (0)1473 836200 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information mation and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2023 Antistat.



INSTALLATION

- 1. Check that you have received all parts: monitor, power/ground adapter and the adhesive pad.
- 2. Using the pad, mount the monitor under the work bench. (Other suggested mounting locations include the bench top and under bench shelving.)
- 3. Plug in the power/ground adapter.

OPERATION

- 1. Place a wristband on your wrist and plug the coiled cord banana plug into the monitor's banana jack. The monitor will display a green light when a functional wrist strap with good skin contact is connected to the unit.
- 2. Connect the monitor to the dual jack socket.
- 3. Connect dual jack socket to earth bonding plug.
- 4. The unit will sound an alarm and display a red light if the wrist strap becomes defective or if the person is not in contact with the wristband.
- 5. Unplug the wrist strap coiled cord from the unit to stop the alarm.
- 6. Monitor will alarm if the continuity from the monitor to the mat to ground is lost.

CALIBRATION

The monitor is calibrated to standards traceable to NIST. Frequency of re-calibratrion should be based on the critical nature of those ESD sensitive items handled and the risk of failure for the ESD protective equipment and materials.

To request a quotation or for more information, please call +44 (0)1473 836200 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information mation and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2023 Antistat.